



Pumps & Garden


• Ecop®	
Surface pumps	page 284
Booster sets	page 284
Drainage clear water pump	page 284
Sewage pump	page 284
• Manual pumps	page 285
• Spid'O®	
Pumps accessories	page 285
Pump plastic couplings	page 286
Gear clamps	page 286
Garden brass fluted fittings	page 287
Garden brass quick fittings	page 287
Garden ABS plastic quick fittings	pages 288 to 289
SPRING - Surface pumps & booster set	page 290
STORM - Drainage & sewage pumps	page 291
Surface pumps	page 292
Booster sets	page 292
Drainage clear water pump	page 293
Sewage pumps	page 293
Dirty water pumps	page 293
Well pump	page 294
Borehole pumps Ø 4"	page 294
Portable engine driven pumps (SP 95)	page 294
Gas oil transfer pump	page 294
Swimming pool pumps	page 295
Swimming pool pump fittings	page 295
Pool pump	page 295
Rainwater pumps & manifolds	page 295
• Spid'O Pro® pumps	
Surface pumps	page 296
Booster sets	page 296
Sewage pumps	page 297
Borehole pump Ø 4"	page 297
• Zenit® pumps	
Drainage pumps	page 298
Dirty water pumps	page 299
Grinder dirty water pumps	page 299
• BBC® pumps	
Drainage pumps - High-head	page 300
Dirty water pumps	pages 300 to 301
Grinder dirty water pumps	page 301
Well pumps	page 301
• Tsurumi® pumps	
Drainage pumps	page 302
Sandy & muddy water pumps	page 302
Sewage pump	page 302
• T-Water® pumps	
Borehole pumps Ø 4"	page 303
Set for borehole or well domestic installation	page 303
Borehole pumps accessories	page 304
• DAB® pumps	
Self-priming pumps	pages 304 to 305
Peripheral pumps	page 305
Booster sets	page 305
Drainage pumps	page 306
Sewage pump	page 306
Well pumps	page 306
• Lifting stations	
Wastewater lifting stations	page 307
Sewage & dirty water lifting stations	pages 308 to 309
• Transfer pumps	
Liquid transfer pumps	page 310
Oil transfer pumps	page 310
Gas oil transfer pumps	pages 310 to 311
• Control panels	
For surface pumps	page 312
For 1 pump drainage/sewage/dirty water	page 312
For 2 pumps drainage/sewage/dirty water	page 312
For well & borehole pumps	pages 312 to 313
Control panel accessories	page 313
• Pressurised water tanks	
Membrane tanks	page 314
Diaphragm tanks	page 315
• Automatic devices for domestic pumps	page 316
• Pressure switches	page 317
• Level control	
Level switches	page 318
Level monitors	page 318
Level detectors	page 318
• Pumps accessories & fittings	page 319
• Manometers	page 320

Surface pumps



Pallet of 48 pcs


sold by 2 pcs


Ecop 150

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
600 0,8	1~230	2,8	32	5	002002

Pallet of 40 pcs


sold by 2 pcs


Ecop 140

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
600 0,8	1~230	3,5	35	5	002020

Pallet of 30 pcs

sold by 2 pcs


Ecop 160


power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
1000 1,3	1~230	3,6	42	5	002040

Booster sets


HidroTOM
 1152 Budapest, Városcapu u. 3.
 Tel./Fax: +361415-0802, -03 Mobil: +36309449620
 www.hidroton.hu, E-mail: hidroton@hidroton.hu
 5350 Tiszafüred Őz u. 15.




Pallet of 18 pcs


Ecop 140/20

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
600 0,8	1~230	3,6	35	5	20	002161

Pallet of 18 pcs


Ecop 160/20


power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
1000 1,3	1~230	3,6	42	5	20	002120

Drainage clear water pump



Pallet of 72 pcs

sold by 4 pcs


Ecop 100 automatic


power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	code
250 0,3	1~230	6	6,8	002236

Sewage pump



Pallet of 72 pcs

sold by 4 pcs


Ecop 105 automatic

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	code
400 0,5	1~230	9	5,5	002237

Manual pumps



	max. flow (m³/h)	max. height (m)	suction Ø	code
MA 9	0,9 to 1,2	3 to 4	1"	002860

	max. flow (m³/h)	max. height (m)	suction Ø	code
MA 12	1,2	6 to 7	1"1/4	002875

	max. flow (m³/h)	max. height (m)	suction Ø	code
MA H	1,2 to 1,8	1	1 m steel plunger	002880

Includes 2 m pipe, Ø 20 mm.



**Metal
extension**

	code
M 1"	051160
M 1"1/4	051175



Foot for MA 12

	code
	002876



Pumps accessories



Plastic suction set	PVC pipe - Food quality & safety - Includes Plastic check valves & strainer.

length (m)	Ø pipe	Ø	code
4	22	F 1"	003000
7	22	F 1"	003005



Brass suction set	PVC pipe - Food quality & safety - Includes brass fitting & check valve, stainless steel strainer.

length (m)	Ø pipe	Ø	code
5	22	F 1"	003010
7	22	F 1"	003020



Metal suction set	PVC pipe - Food quality & safety - Includes brass fitting & check valve, stainless steel strainer, aluminium socket.

length (m)	Ø pipe	Ø	code
7	25	F 1"	003025
7	30	F 1"1/4	003030



Universal drainage set	For all drainage/sewage/dirty water pumps PVC pipe.

length (m)	Ø pipe	Ø	code
5	25	F 1"1/4	002200
5	32	F 1"1/2	002205



Hydrotech 200	Lack of water & hammer protection - For 1~230V surface pumps (max. power: 1,3 kW) - Max. pressure: 10 bar - Max. flow: 5 m³/h - Connections MM 1".

	code
	003190

NEW




Brio 2000 M	Lack of water protection device - For surface & submersible pumps with pressure over 1,5 bar (max. power: 1,2 kW) - Max. pressure: 10 bar - Connections FM 1" - 1,5 m wire.

	code
	003251

HTX	Lack of water protection device - Manual resetting (restart) - For surface pumps (1~230V, 3 A to 8 A) - Temperature: 5°C to 45°C.

	code
	003161



Garden brass fluted fittings

2 piece hose nozzle w/ captive gasket



Ø	1/2"-13	3/4"-15	3/4"-19	1"-19	1"-25	1"1/4-30
code	290401	290501	290511	290611	290621	290731

Male fitting



Ø	1/2"-13	3/4"-15	3/4"-19	1"-25	1"1/4-30
code	293401	293501	293511	293621	293731

3 piece w/ captive gasket



Ø	1/2"-13	3/4"-15	3/4"-19	1"-25	1"1/4-30
code	292401	292501	292511	292621	292731

2 piece elbow



Ø	3/4"-15	1"-19
code	290001	290011

Tee



Ø	15	19
code	296001	296011

Spare gaskets (sold by 10)



Ø	1/2"-13	3/4"-15	3/4"-19	1"-19	1"-25	1"1/4-30
code	290139	290159	290199	290209	290259	290309



Hose nozzle



Ø	3/4"-20	1"-25	1"1/4-30
code	263151	263161	263171

Nipple



Ø	15	19	25
code	294001	294011	294021

Elbow w / free nut



Ø	1/2"-13 to 15	3/4"-15 to 19
code	290101	290201

Water-hose nozzle



Ø	15	19
code	298001	298021

Y junction



F3/4" - M3/4"

code	
297551	

Y junction w/ shut-off valves



F3/4" - M3/4"

code	
297001	

Garden brass quick fittings

Compatible with ABS plastic quick fittings (pages 288 & 289).

Coupling



Ø	15	19
code	291101	291111

Coupling w/ stop pipe



Ø	15	19
code	291201	291211

Hose coupling nipple



Ø	15	19
code	291301	291311

Adaptor male



Ø	3/4"
code	291021

Elbow w/ free nut



Ø	1/2"	3/4"
code	291241	291251

Nipple



Ø	15	19
code	291131	291231

Adaptor female



Ø	1/2"	3/4"	1"
code	291041	291051	291061

Double connection



code	
291401	

Water-hose nozzle



code	
291421	

Y junction



code	
291411	

Y junction w/ shut-off valves



F3/4"

code	
291431	

Spare gaskets (sold by 10)



code	
291009	



bulk blister packaging

Garden ABS plastic quick fittings



High flow automatic fitting

Int. Ø 19 mm

blister code

295811



High flow female adaptor

Int. Ø F1"-1"

blister code

295271



Adaptor for nozzle valve

For Ø 15 to 17 mm nozzle

blister code

295301



Male coupling

Int. M3/4"

blister code

295451



Coupling

bulk code

295904

blister code

295901



3 way junction

bulk code

295914

blister code

295911



Valve nozzle

F1/2"-3/4"
F3/4"-1"

bulk code

295254
295264

blister code

295251
295261



2 way valve nozzle w/ shut-off valves F1/2"

blister code

295921



Female coupling

Ø 15 mm
Ø 19 mm

bulk code

295504
295514

blister code

295501
295511



Multijet water-hose nozzle

bulk code

298304

blister code

298301



Female coupling with aquastop

Ø 15 mm
Ø 19 mm

bulk code

295604
295614

blister code

295601
295611



Nipple

Ø 15 mm
Ø 19 mm

bulk code

295704
295714

blister code

295701
295711



Multijet gun

Adjustable flow jet
Blocking trigger

bulk code

298204

blister code

298201



Multijet gun

Adjustable direction and flow jet
Blocking trigger
Anti-slip handle

blister code

298211



Multijet gun set

Includes: 1 valve nozzle F 1/2"-3/4"
+ 1 quick fitting
+ 1 aquastop quick fitting
for pipe Ø 15 mm
for pipe Ø 19 mm

blister code

298331
298341



Multijet gun

Adjustable direction and flow jet
Blocking trigger
Anti-slip handle
Metal head

blister code

298221

HidroTOM
1152 Budapest, Városcapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidrotom.hu, E-mail: hidrotom@hidrotom.hu
5350 Tiszafüred Őz u. 15.



Spray gun 6 jets

Adjustable flow
Blocking trigger

bulk code	blister code
298104	298101



Spray gun set

Includes: 1 valve nozzle F1/2"-3/4"
+ 1 quick fitting
+ 1 aquastop quick fitting



for pipe Ø 15 mm
for pipe Ø 19 mm

blister code
298351
298361



Spray gun

8 jets
Adjustable flow
Blocking trigger
Anti-slip handle

blister code
298111



Spray gun

7 jets
Adjustable flow
Blocking trigger
Anti-slip handle
Metal head

blister code
298121



Sprinkler

blister code
298651



Rotary sprinkler 3 jets

blister code
298641



Watering pipe

25 m length - 23 bar -
3 layers - Textile
wrapped with polyester -
2 years guarantee

Ø int.	15 mm
code	005152



Watering pipe - Anti-twist

25 m length - 22 bar -
4 anti-twist layers -
Textile knitted with
polyester -
10 years guarantee

Ø int.	15 mm	19 mm
code	006152	006192



90 cm multijet water-hose nozzle

Shower jet


blister code
298501



Adjustable multijet water-hose nozzle

7 jets
90 cm to 135 cm adjustable
Adjustable flow
Anti-slip handle
Adjustable head

blister code
298511



Adjustable multijet water-hose nozzle

7 jets
90 cm to 135 cm adjustable
Adjustable flow
Blocking trigger
Anti-slip handle
Metal adjustable head

blister code
298521



Swinging sprinkler 15 jets (150 m²)

Adjustable swing angle

blister code
298601



Swinging sprinkler 19 jets (220 m²)

Adjustable swing angle
Brass outlets

blister code
298611

695 - Watering box


With angle brass ball valve

Ø	15	20
male outlet	3/4"	1"
female hose	3/4"+1/2"	3/4"
code	695015	695020



Surface pumps

Comfort & simplicity




Pallet of 18 pcs

Spring 900

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
900	1,2	1~230	3,6	42	8	002070

High performance




Pallet of 18 pcs

Spring 1100

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
1100	1,5	1~230	4,6	46	8	002071

HidroTOM
1152 Budapest, Városcsú u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidroto.hu, E-mail: hidroto@hidroto.hu
5350 Tiszaliget 02 u. 15.

Super power - Lack of water protection



Pallet of 18 pcs

Spring 1300 automatic

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
1300	1,7	1~230	5	46	8	002172



Fully automatised
water
management
system.




Built-in
automation
& safety
mechanism.



Lack of water
protection: shut-off
in case of outlet
valve closing.

Booster set

Automatic solution - Constant pressure & flow



Pallet of 8 pcs

Spring 1100/24

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
1100	1,5	1~230	4,6	45	8	24	002171



Interchangeable
membrane.




Built-in manometer
for pressure control.





Drainage & sewage pump



Manual/
automatic
switch.



Clear water.



Sewage water.

Pallet of 34 pcs


Storm CDW 400

power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction	max. particles diameter (mm)	outlet Ø	code
400	0,5	1~230	7	5	5 mm - clear water 25 mm - waste water	25	1"1/2 M 002250

Includes 3 m rope.



Drainage clear water pumps



Manual/automatic switch.


HidroTOM
1152 Budapest, Városcapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidroTOM.hu, E-mail: hidroTOM@hidroTOM.hu
5390 Tiszaföld Öz u. 15.

Pallet of 34 pcs

Storm CW 550

power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (mm)	max. particles diameter (mm)	outlet Ø	code
550	0,7	1~230	10	8	1	5	1"1/2 M 002251

Includes 3 m rope.



Sensor: adjustable probe
with automatic on/off function
at the user given water level.

Pallet of 34 pcs


Storm CW 750

power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (mm)	max. particles diameter (mm)	outlet Ø	code
750	1,0	1~230	13	9	1	5	1"1/2 M 002252

Includes 3 m rope.



Sewage pumps




Manual/automatic switch.

Pallet of 34 pcs

Storm DW 550

power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (mm)	max. particles diameter (mm)	outlet Ø	code
550	0,7	1~230	10	7	6	30	1"1/2 M 002247

Includes 3 m rope.




Sensor: adjustable probe
with automatic on/off function
at the user given water level.

Pallet of 34 pcs

Storm DW 750

power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (mm)	max. particles diameter (mm)	outlet Ø	code
750	1,0	1~230	12	8	6	30	1"1/2 M 002248

Includes 3 m rope.



Sensor: adjustable probe
with automatic on/off function
at the user given water level.

Pallet of 34 pcs

Storm DW 900


power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (mm)	max. particles diameter (mm)	outlet Ø	code
900	1,2	1~230	15	9,5	6	30	1"1/2 M 002249

Includes 3 m rope.

NEW



Surface pumps




Jetcom 550 pack

Includes 4 m suction set, check valve, quick fittings F1" & F Ø15, aquastop quick fitting Ø15, 20m watering pipe, water-hose nozzle with quick connection.

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
550 0,7	1~230	2,8	42	8	002056

Pallet of 24 pcs



Jetinox 800

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
800 1,1	1~230	3,3	46	9	002064


Pallet of 40 pcs



AF 100



AF 130




— AF 100

— AF 130

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
1000 1,3	1~230	4	45	8	002034
1300 1,7	1~230	5,5	48	8	002039


Pallet of 30 pcs



AMX 50/4

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
1100 1,5	1~230	5,4	48	8	002745

Pallet of 18 pcs




K 800 automatic

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
800 1,1	1~230	3,3	46	9	002164

Pallet of 40 pcs

Includes automatic & lack of water protection device & built-in manometer.

Booster sets




BF 100/20

BF 100/50

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
1000 1,3	1~230	4	45	8	24	002142
1000 1,3	1~230	4	45	8	50	002155

BF 100/20: pallet of 18 pcs

BF 100/50: pallet of 8 pcs




BMX 4/24

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
1100 1,5	1~230	5,4	48	8	24	002186

Pallet of 14 pcs



Drainage clear water pump




Pallet of 72 pcs

	power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Inox EC 170	750	1,0	1~230	10	9	15	1"1/4 F	002243



Sewage pumps


HidroTOM
1152 Budapest, Városkapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidrotoom.hu, E-mail: hidrotoom@hidrotoom.hu
5350 Tiszafüred Őz u. 15.



Pallet of 72 pcs

	power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Inox ECC 190	750	1,0	1~230	11	8	45	1"1/2 F	002227

Passing through Ø 30 mm.




Pallet of 40 pcs

	power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Inox ECC Pro 300	1200	1,6	1~230	19,5	10,5	55	1"1/2 M	002253

With Vortex stainless steel impeller - Passing through Ø 40 mm.




Dirty water pumps



Pallet of 60 pcs

	power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Inox EV 300	580	0,8	1~230	18	9		1"1/2 F	002244

Passing through Ø 35 mm.



Pallet of 40 pcs

	power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Inox ECC Pro 400	1500	2,0	1~230	24	11	55	2" F	002254

With Vortex stainless steel impeller - Passing through Ø 40 mm.



Well pump



B 90/3


Includes 10 m rope.

power supply (W)	voltage (hp)	max. flow (m³/h)	max. height (m)	max. submersion depth (m)	pump Ø (mm)	outlet Ø	code
950	3,1	1~230	6	34	10	157	1"1/4 M 002509

Pallet of 40 pcs



Borehole pumps Ø 4"



— Subinox 6

— Subinox 7

Includes starting panel, electric cable & 20 m rope.

power supply (W)	voltage (hp)	max. flow (m³/h)	max. height (m)	max. submersion depth (m)	outlet Ø	code
800	1,1	1~230	5,4	48	20	1"1/4 F 002306
900	1,2	1~230	5,5	56	20	1"1/4 F 002307


Pallet of 40 pcs

HidroTOM
1152 Budapest, Városház u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidroTOM.hu, E-mail: hidroTOM@hidroTOM.hu
5350 Tiszafüred Őz u. 15.



Control panels Micro DSN & Micro DSE, see pages 312 & 313

Portable engine driven pumps (SP 95)



T 414

Inlet and outlet M 1".

power supply (hp)	max. flow (m³/h)	max. height (m)	max. suction (m)	fuel tank (l)	code
2,1	10	36	5	1,3	002814

Pallet of 24 pcs



T 435

Inlet M 1"1/2 and outlet M 1"1/2 or M 1".

power supply (hp)	max. flow (m³/h)	max. height (m)	max. suction (m)	fuel tank (l)	code
5,6	25	6	6	3,6	002835

Pallet of 12 pcs

Gas oil transfer pump

For gas oil, fuel oil & biofuel.

power supply (W)	voltage (hp)	max. flow (m³/h)	max. pressure (bar)	code
500	0,7	1~230	2,1	3,5 002650

Includes 2 m suction set with M1" connections & check valve, gas oil nozzle, 4 m pipe with connections.



Swimming pool pumps



Pallet of 30 pcs



PC 300

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	code
300 0,4	1~230	7	10	002960

For aboveground pool (5 to 25 m³).



PC 500

power supply (W) (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	code
500 0,7	1~230	2	9	10	002961

For 20 to 45 m³ pool.



PC 800

power supply (W) (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	code
800 1,1	1~230	3,2	15	15	002962

For 40 to 90 m³ pool.

Swimming pool pump fittings



PVC reduced nipple

code
F1"1/4 - M1"
F1"1/2 - M1"1/4
F2" - M1"1/2
F2"1/2 - M2"



PVC fitting to be glued

code
F1"1/2 - M50 - F40
M1"1/2 - M50 - F40



PVC free nut nozzle

code
F1"1/4 - Ø 27 or 25
F1"1/2 - Ø 32 or 30
F2" - Ø 42 or 40
F2"1/4 - Ø 52 or 50



EPDM flat gasket

code
1"
1"1/4
1"1/2
2"
2"1/4



Pool pump



Pallet of 64 pcs

ECC 150

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	code
320 0,4	1~230	7,5	6	002217

Vertical or horizontal position - Includes: support for horizontal position.

Rainwater pumps & manifolds



Pallet of 200 pcs



E 160

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
80 0,1	1~230	3	3	3	3/4" M	002201

Pallet of 80 pcs

EC 300

power supply (W) (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
350 0,5	1~230	3	10	3	3/4" M	002800



Sand


Universal: can be mounted on any diameter of zinc, PVC or copper gutter (from Ø 80 to 110 mm) - Easy mounting: without any cutting or removing of gutter - Ready to be mounted: supplied with a drilled saw.

code
050646
050645

Grey

NEW



Surface pumps


Jetinox 550 kit

Includes 4 m suction set with check valve.


power supply (W)	voltage (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max.suction (m)	code
550	0,7	1-230	2,4	2,9	42	9	002051

Pallet of 48 pcs


Jetinox 1200

power supply (W)	voltage (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max.suction (m)	code
1200	1,6	1-230	5,2	4,5	50	9	002074

Pallet of 50 pcs



Plurinox 1200

power supply (W)	voltage (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max.suction (m)	code
1200	1,6	1-230	5,2	6	55	8	002756

Pallet of 50 pcs

NEW



Booster sets


X80/20 Protec

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max.suction (m)	tank (l)	code
800	1,1	1~230	3,3	46	9	22	002136


Pallet of 18 pcs


HidroTOM
 1152 Budapest, Városháza u. 3.
 Tel./Fax: +361415-0802, -03 Mobil: +36309449620
 www.hidotom.hu, E-mail: hidotom@hidotom.hu
5396 Tiszaliget Dc u. 15.


X120/50 Protec

power supply (W)	voltage (hp)	amp. (V-50Hz)	(A)	max. flow (m³/h)	max. height (m)	max.suction (m)	tank (l)	code
1200	1,6	1~230	5,2	4,4	50	9	50	002156


Pallet of 18 pcs

NEW

Maxinox 500

Passing through Ø 25 mm.

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	outlet Ø	code
500	0,7	1~230	10,5	7	1" 1/4 M	002213

Pallet of 96 pcs



Maxinox 700

Passing through Ø 30 mm.

power supply (W)	power supply (hp)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	outlet Ø	code
700	0,9	1~230	18	8	1" 1/2 M	002214

Pallet of 72 pcs

NEW

Borehole pump Ø 4"

50/8 Auto

Includes starting panel & lack of water protection, electric cable & 20 m rope.

power supply (W)	power supply (hp)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max.submer depth (m)	outlet Ø	code
1100	1,5	1~230	4,8	6	57	20	1" F	002518

Pallet of 40 pcs

1152 Budapest, Városcapu u. 3.


Tel./Fax: +361415-0802, -03 Mobil: +36309449620

www.hidrotom.hu, E-mail: hidrotom@hidrotom.hu

5350 Tiszafüred Öz u. 15.




Drainage pumps




	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
— DR Blue 40 automatic	300	1~230	2,3	10,8	7	77	1"1/4 F	137004
— DR Blue 50 automatic	370	1~230	2,8	14,4	9,5	77	1"1/4 F	137005
— DR Blue 75 automatic	550	1~230	4,1	14,4	12	77	1"1/4 F	137007
— DR Blue 100 automatic	750	1~230	5,6	18	14,2	77	1"1/4 F	137010

Max. particles 7 mm - Includes 10 m cable.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
— DR Blue Pro 50 automatic	370	1~230	2,8	14,4	8,7	77	1"1/4 F	137205
— DR Blue Pro 75 automatic	550	1~230	4,1	14,4	12,3	77	1"1/4 F	137207
— DR Blue Pro 75 T	550	3~400	1,6	14,4	12,3	77	1"1/4 F	137208
— DR Blue Pro 100 automatic	750	1~230	5,6	18	14,6	77	1"1/4 F	137210
— DR Blue Pro 100 T	750	3~400	2,2	18	14,6	77	1"1/4 F	137211
— DR Blue Pro 150 automatic	1100	1~230	7,5	36	14,4	77	2" F	137215
— DR Blue Pro 150 T	1100	3~400	3,2	36	14,4	77	2" F	137216
— DR Blue Pro 200 automatic	1500	1~230	10	36	17	77	2" F	137218
— DR Blue Pro 200 T	1500	3~400	4,3	36	17	77	2" F	137219

Max. particles 15 mm - Includes 10 m cable.




HidroTOM
1152 Budapest, Városcapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidrotoom.hu, E-mail: hidrotoom@hidrotoom.hu
5350 Tiszafüred Öz u. 15.

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	passing through (mm)	outlet Ø	code
— DR-Steel 25 M automatic	250	1~230	2,3	7,2	8,5	10	1"1/4 F	137608
— DR-Steel 37 M automatic	370	1~230	3,1	9	13,6	10	1"1/4 F	137610
— DR-Steel 55 M automatic	550	1~230	4,3	18,1	12,4	12	1"1/2 F	137612
— DR-Steel 75 M automatic	750	1~230	5,6	19,9	16	12	1"1/2 F	137614
— DR-Steel 75 M*	750	1~230	5,6	19,9	16	12	1"1/2 F	137615
— DR-Steel 75 T	750	3~400	2,4	19,9	16	12	1"1/2 F	137616

Max. particles 10 mm for DR 25 & DR 37, 12 mm for DR 55 & DR 75 - Includes 10 m cable.

* Without level switch.




	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
AP Blue Pro 200 automatic	1500	1~230	10	25,2	26,6	1"1/2	137431
AP Blue Pro 200 T	1500	3~400	4,3	25,2	26,6	1"1/2	137435

Max. particles 6 mm - Includes 10 m cable.

For non automatic pumps: - control panels, see pages 312 & 313
- level switches, see page 318


Dirty water pumps



- DG Blue 40 automatic
- DG Blue 50 automatic
- DG Blue 75 automatic
- DG Blue 100 automatic

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
300	1~230	2,3	14,4	6	122	1"1/2 F	137104
370	1~230	2,8	18	7,6	122	1"1/2 F	137105
550	1~230	4,1	21,6	10,1	122	1"1/2 F	137107
750	1~230	5,6	25,2	11,6	122	1"1/2 F	137110

Passing through Ø 40 mm - Includes 10 m cable.




NEW
NEW
NEW
NEW

- DG Blue Pro 50 automatic
- DG Blue Pro 75 automatic
- DG Blue Pro 75 T
- DG Blue Pro 100 automatic
- DG Blue Pro 100 T
- DG Blue Pro 150 automatic
- DG Blue Pro 150 T
- DG Blue Pro 200 automatic
- DG Blue Pro 200 T

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
370	1~230	2,8	18	7	122	1"1/2 F	137305
550	1~230	4,1	21,6	10,2	122	1"1/2 F	137307
550	3~400	1,6	21,6	10,2	122	1"1/2 F	137308
750	1~230	5,6	25,2	11,4	122	1"1/2 F	137310
750	3~400	2,2	25,2	11,4	122	1"1/2 F	137311
1100	1~230	7,5	36	12,3	122	2" F	137315
1100	3~400	3,2	36	12,3	122	2" F	137316
1500	1~230	10	43,2	15,3	122	2" F	137318
1500	3~400	4,3	43,2	15,3	122	2" F	137319

Passing through Ø 40 mm - Includes 10 m cable.




- DG-Steel 37 M automatic*
- DG-Steel 55 M automatic
- DG-Steel 75 M automatic
- DG-Steel 75 T

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	passing through (mm)	outlet Ø	code
370	1~230	3,1	10,8	8,7	25	1"1/4 F	137600
550	1~230	4,3	19,9	8,1	40	1"1/2 F	137602
750	1~230	5,6	21,7	10	40	1"1/2 F	137604
750	3~400	2,3	21,7	10	40	1"1/2 F	137606

Passing through Ø 40 mm (except DG 37: Ø 25 mm) - Includes 10 m cable.

* Sewage only.

Grinder dirty water pumps




- GR Blue Pro 150 M*
- GR Blue Pro 150 M automatic*
- GR Blue Pro 150 T
- GR Blue Pro 150 T automatic
- GR Blue Pro 200 M*
- GR Blue Pro 200 M automatic*
- GR Blue Pro 200 T
- GR Blue Pro 200 T automatic

power supply (kW)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
1,1	1~230	7,5	18	21,1	1"1/2	137520
1,1	1~230	7,5	18	21,1	1"1/2	137521
1,1	3~400	3,2	18	21,1	1"1/2	137525
1,1	3~400	3,2	18	21,1	1"1/2	137526
1,5	1~230	10	18	27	1"1/2	137530
1,5	1~230	10	18	27	1"1/2	137531
1,5	3~400	4,3	18	27	1"1/2	137535
1,5	3~400	4,3	18	27	1"1/2	137536

Includes 10 m cable.

* Includes starting panel.



Drainage pumps - High-head




Semisom 130 H automatic*
Semisom 130 H M*
Semisom 130 H T

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
1100	1~230	7,6	6	30	1"1/2 F	132001
1100	1~230	7,6	6	30	1"1/2 F	132002
1100	3~400	2,9	6	30	1"1/2 F	132005

Max. particles 5 mm - Includes 10 m cable.

* Includes starting panel.


Dirty water pumps



Semisom 265 automatic vertical outlet
Semisom 290 automatic horizontal outlet
Semisom 290 M + SP horizontal outlet*
Semisom 290 M horizontal outlet
Semisom 290 T horizontal outlet
Semisom 290 T automatic horizontal outlet

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
550	1~230	4,2	12	8	200	1"1/2 F	132038
550	1~230	4,2	12	8	200	1"1/2 F	136039
550	1~230	4,2	12	8	200	1"1/2 F	136040
550	1~230	4,2	12	8	200	1"1/2 F	136050
550	3~400	1,7	12	8	200	1"1/2 F	136045
550	3~400	1,7	12	8	200	1"1/2 F	136047

Passing through Ø 40 mm for Semisom 265 & Ø 50 mm for Semisom 290 - Includes 10 m cable. * Includes starting panel.




Semisom 490 automatic vertical outlet
Semisom 490 automatic horizontal outlet
Semisom 490 M + SP horizontal outlet*
Semisom 490 M horizontal outlet
Semisom 490 T horizontal outlet
Semisom 490 T automatic horizontal outlet

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
1100	1~230	7,3	29	10	200	2" F	136073
1100	1~230	7,3	29	10	200	2" F	136079
1100	1~230	7,3	29	10	200	2" F	136075
1100	1~230	7,3	29	10	200	2" F	136081
1100	3~400	2,7	29	10	200	2" F	136076
1100	3~400	2,7	29	10	200	2" F	136071

Passing through Ø 50 mm - Includes 10 m cable.

* Includes starting panel.





Semisom 500/50 M*
Semisom 500/50 T
Semisom 800/50 M*
Semisom 800/50 T
Semisom 900/50 M*
Semisom 900/50 T
Semisom 1000/50 T

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
1100	1~230	9,2	30	9,5	275	2" F	132100
1100	3~400	3,3	30	9,5	275	2" F	132105
1500	1~230	11,4	30	12	275	2"1/2 F	132110
1500	3~400	4	30	12	275	2"1/2 F	132115
1500	1~230	11,4	48	16	275	2"1/2 F	132120
1500	3~400	4	48	16	275	2"1/2 F	132125
2200	3~400	5,9	54	19,5	275	2"1/2 F	132135

Passing through Ø 50 mm - Includes 10 m cable.

* Includes starting panel.




Semisom 650 M*
Semisom 650 T
Semisom 650 T automatic

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
1,5	1~230	12	36	8,5	275	2"1/2 F	132082
1,5	3~400	4,6	36	8,5	275	2"1/2 F	132075
1,5	3~400	4,6	36	8,5	275	2"1/2 F	132076

Passing through Ø 65 mm - Includes 10 m cable.


* Includes starting panel.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
— Semisom 754/65 M*	1200	1~230	7,7	42	7,3	275	3" F	132140
— Semisom 754/65 T	1200	3~400	3,3	42	7,3	275	3" F	132145
— Semisom 1100/65 T	2200	3~400	6	48	12	275	3" F	132155
— Semisom 1300/65 T	3400	3~400	8,1	54	17	275	3" F	132165
— Semisom 1500/65 T	3400	3~400	9	78	17,5	275	3" F	132175

Passing through Ø 65 mm - Includes 10 m cable.

* Includes starting panel.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
— Semisom 1504/80 T	2600	3~400	8,1	84	8,7	275	3"	132895
— Semisom 1055/80 T	4100	3~400	9,2	60	16,5	275	3"	132805
— Semisom 1675/80 T	5500	3~400	12	96	18,3	275	3"	132845
— Semisom 2100/80 T	7500	3~400	16	120	20,1	275	3"	132885
— Semisom 1200/80 T	7500	3~400	16	72	25,7	275	3"	132865


Passing through Ø 74 mm - Includes 10 m cable.



	code
Fork hook	455028
Foot pad*	455029
Discharge flange	455035



For non automatic pumps: - control panels, see pages 312 & 313
- level switches, see page 318



Grinder dirty water pumps



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	code
Semisom 125 GR M aut.*	1800	1~230	9,2	6,5	31	132013
Semisom 125 GR M*	1800	1~230	9,2	6,5	31	132014
Semisom 125 GR T	1500	3~400	2,9	6,5	30	132015

Includes 10 m cable.

* Includes starting panel.




Well pumps



	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. submersion depth (m)	pump Ø (mm)	outlet Ø	code
— Turbosom 57 M*	550	1~230	2,4	60	10	136	1" F	151020
— Turbosom 77 M*	750	1~230	2,4	84	10	136	1" F	151030
— Turbosom 77 T	750	3~400	2,4	85	10	136	1" F	151035

Supplied with 15 m cable and 15 m rope.



	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	max. submersion depth (m)	pump Ø (mm)	outlet Ø	code
— SRM 4/100 automatic*	650	1~230	6	46	30	130	1"1/4 F	150603
— SRM 4/100 M*	650	1~230	6	46	30	130	1"1/4 F	150602
— SRM 6/100 automatic*	950	1~230	6	69	30	130	1"1/4 F	150609
— SRM 6/100 M*	950	1~230	6	69	30	130	1"1/4 F	150608
— SRT 6/100 T	950	3~400	6	69	30	130	1"1/4 F	150610
— SRM 7/100 automatic*	1200	1~230	6	80	30	130	1"1/4 F	150612
— SRM 7/100 M*	1200	1~230	6	80	30	130	1"1/4 F	150611
— SRT 7/100 T	1200	3~400	6	80	30	130	1"1/4 F	150613


Supplied with 15 m cable and 15 m rope.

* Includes starting panel.

Control panels Micro DSN & Micro DSE, see pages 312 & 313




Drainage pumps



Oma 3

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
150	1~230	1,6	10	7,5	1"1/4 F	133096

Max. particles 10 mm - Includes 10 m cable.




LSC1-4S

LSC E1-4S*

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
480	1~230	2,9	10	11	1" F	133100
480	1~230	2,9	10	11	1" F	133099

For complete drying surface - Max. particles 6 to 1 mm - Includes 10 m cable, gear clamp & 25 mm fitting.

* Pre-equipped for automatism with min. 1 mm suction height level switch.



LB-480 A

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
480	1~230	2,9	13	11	2" M	133107


Max. particles 6 mm.

Sandy & muddy water pumps



HidroTOM

1152 Budapest, Városház u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidrotoom.hu, E-mail: hidrotoom@hidrotoom.hu
5350 Tiszaliget Oz u. 15.




HS2-4S

HS2-75S

HS3-75S

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
400	1~230	2,6	11	12	2" M	133101
750	1~230	4,6	13	18	2" M	133106
750	1~230	4,6	18	18	3" M	133102

Max. particles 7 mm - Includes 10 m cable.




HS2-4S set

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
400	1~230	2,6	11	12	2" M	133103

Max. particles 7 mm - Includes HS2-4S pump, 20 m pipe Ø 20 mm & case - Dimension (mm): L 58 x I 28 x H 43.

Sewage pump



Poma

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	outlet Ø	code
150	1~230	1,6	12,5	6	2" F	133097

Max. particles 35 mm - Includes 10 m cable.


For non automatic pumps:

- control panels, see pages 312 & 313

- level switches, see page 318

Borehole pumps Ø 4"

TW SUB 50/11 M & T supplied with 30 m cable & 30 m nylon rope -
TW SUB 50/16 M & T supplied with 40 m cable & 40 m nylon rope - Made in Germany.



- TW SUB 50/11 M
- TW SUB 50/11 T
- TW SUB 50/16 M
- TW SUB 50/16 T


	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	outlet Ø	code*	code**
TW SUB 50/11 M	750	1~230	4,8	64	1"1/4 F	151619	151621
TW SUB 50/11 T	750	3~400	4,8	64	1"1/4 F	151628	151627
TW SUB 50/16 M	1100	1~230	4,8	97	1"1/4 F	151629	151631
TW SUB 50/16 T	1100	3~400	4,8	97	1"1/4 F	151638	151637

* Includes starting panel in 1~230 V versions.

** Includes control panel & lack of water protection in 1~230 V & 3~400 V versions.

Set for borehole or well domestic installation

1800 to 3000 l/h flow for 4 to 5 people water use & 1000 m² watering.



30 m maximum depth

Water level	Flow
15 m	1800 l/h at 4 bar - 3000 l/h at 3 bar
20 m	1800 l/h at 3,5 bar - 3000 l/h at 2,5 bar
25 m	1800 l/h at 3 bar - 3000 l/h at 2 bar

1 Pump 1~230 V (TW SUB 50/11 M)

2 Includes panel, 30 m cable & 30 m rope

or

1 Pump 3~400 V (TW SUB 50/11 T)

2 Includes panel 30 m cable & 30 m rope

+

3 Vertical tank 100 l

4 Pressure switch XMP 6 PM

5 Manometer 0-6 bar

6 Check valve 1"1/4

7 Tight cap 1"1/4

code

151621

151627

code

309100

412506

413106

305007

551502

40 m maximum depth

Water level	Flow
25 m	3000 l/h at 4,5 bar - 3500 l/h at 3 bar
30 m	3000 l/h at 4 bar - 3500 l/h at 2,5 bar
40 m	3000 l/h at 3 bar - 3500 l/h at 1,5 bar

1 Pump 1~230 V (TW SUB 50/16 M)

2 Includes panel, 40 m cable & 40 m rope

or

1 Pump 3~400 V (TW SUB 50/16 T)

2 Includes panel, 40 m cable & 40 m rope

+

3 Vertical tank 200 l

4 Pressure switch XMP 6 PM

5 Manometer 0-6 bar

6 Check valve 1"1/4

7 Tight cap 1"1/4

code

151631

151637

code

309200

412506

413106

305007

551502

NEW

WHIGS TECHNOLOGY
EQUIPEMENTS POUR LES BÂTIMENTS DE PISCINE

7 Borehole tight cap 1"1/4

For borehole Ø 90 to 140 mm -

Includes tight gaskets -

Max. pump depth: 120 m -

Max. weight: 500 kg.



code

551502

Borehole pumps accessories



Cooling housing for bottom tank

- 1 For TW SUB 50/11M, 50/11T & 50/16T
- 2 For TW SUB 50/16M
- 3 Strainer & gear clamp
- 4 Horizontal support set

length (mm)	code
400	454000
525	454005JE
	454025
	454020

Suspension wire

Ø		code
4 mm	Stainless steel wire*	550004
	Wire clamp	550010
6 mm	Stainless steel wire*	549999
	Wire clamp	550015

* Price/meter.

Franklin motors for Ø 4" pumps

F304 stainless steel casing

power supply (W)	1~230 code	3~400 code
250	190011	190015
370	190022	190026
550	190031	190036
750	190042	190047
1100	190051	190057
1500	190061	190067
2200	190071	190076
3000	-	190086
4000	-	190096
5500	-	190106
7500	-	190107

Includes 1,5 m cable up to 1500W, 2,5 m above.



Starting panel for 1~230V

µF	code
12,5	472010
16	472020
20	472030
30	472040
40	472050
50	472060
70	472070

Cable

length (mm)	code
1,5*	431517
2,5*	431527
2,5**	431528
5*	431529
15***	431715
30***	431730

* Stainless steel 304 connection.

** Stainless steel 316 connection.

*** Brass connection.

DAB® pumps



Self-priming pumps



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
Jet 82 M	600	1~230	3,8	3,6	47	8	016080
Jet 82 T	600	3~400	1,6	3,6	47	8	016085
Jet 102 M	750	1~230	5,1	3,6	54	8	016100
Jet 102 T	750	3~400	1,9	3,6	54	8	016105
Jet 112 M	1000	1~230	6,2	3,6	60	8	016112
Jet 112 T	1000	3~400	2,5	3,6	60	8	016113
Jet 132 M	1000	1~230	6,6	4,8	48	8	016132
Jet 132 T	1000	3~400	2,7	4,8	48	8	016133



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
Jet 151 M	1100	1~230	7,2	4,2	58	8	010150
Jet 151 T	1100	3~400	3	4,2	58	8	010155
Jet 251 M	1850	1~230	10	7,2	60	8	010250
Jet 251 T	1850	3~400	4	7,2	60	8	010255



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
Euro Inox 30/30 M	450	1~230	3,2	3,3	46,0	8	030080
Euro Inox 30/30 T	450	3~400	1,3	3,3	46,0	8	030085
Euro Inox 30/50 M	550	1~230	3,9	4,8	42,2	8	030100
Euro Inox 30/50 T	550	3~400	1,6	4,8	42,2	8	030105
Euro Inox 40/50 M	550	1~230	5,3	4,8	57,7	8	030110
Euro Inox 40/50 T	550	3~400	2,2	4,8	57,7	8	030115
Euro Inox 50/50 M	1000	1~230	6,3	4,8	72	8	030120
Euro Inox 50/50 T	1000	3~400	2,5	4,8	72	8	030125



Multi Inox 3M
Multi Inox 4M
Multi Inox 5M

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
550	1~230	3,7	3,6	34,0	8	030163
750	1~230	4,5	5	46,0	8	030164
1000	1~230	5,5	5	58,0	8	030165

With stainless steel 304 impellers.

Peripheral pumps



KPS 30/16 M
KPS 30/16 T

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	code
300	1~230	2	1,8	32,5	031090
300	3~400	0,9	1,8	32,5	031095

Booster sets



Aquajet 82/20 M
Aquajet 102/20 M
Aquajet 102/60 M

power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	tank (l)	code
600	1~230	3,8	3,6	47	8	20	201029
750	1~230	5,1	3,6	54	8	20	201032
750	1~230	5,1	3,6	54	8	60	201026

Supplied mounted.

E.sybox

NEW



Steady pressure booster set - Includes: self-priming pump, frequency regulator, pressure sensor, flow sensor, LCD screen & expansion tank.

- Economical: energy saving thanks to the frequency regulator - Silent.
- Compact: installation everywhere (even in tiny rooms) - 30% smaller than a traditional set - No additional tank.
- Convenient: easy maintenance & installation - Direct access to the pump stem, the filling cap & the expansion tank.
- Various connections.
- Wireless: up to 4 E.sybox connected.

E.sybox mini
E.sybox

power supply (W)	voltage (V-50Hz)	hp	amp. (A)	max. flow (m³/h)	max. height (m)	max. suction (m)	code
850	1~230	1,1	7	4,2	55	8	209501
1550	1~230	2,1	10	7,2	62	8	209500



Includes float valve, check valve, suction & discharge pipe - E.sydock included
Direct mounting with E.sybox & E.sybox mini.

E.sytank mini
E.sytank

l	code
250	450160
440	450155



E.sybox + E.sydock

E.sydock

code
450151

NEW



Pack E.sytank mini
Pack E.sytank

code
209523
209380



E.sywall

code
450150



2 fittings 1"

code
453089



Drainage pumps



	power supply (W)	Voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Verty Nova 200	220	1~230	6	6,2	3	1" 1/4 M	131003
Verty Nova 400	400	1~230	10	9	3	1" 1/4 M	131004

Built-in level switch - Max. particles 5 mm - Includes 10 m cable.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Nova 180 automatic	220	1~230	1,1	5	5	77	25 mm	131009
Nova 300 automatic	220	1~230	1,5	9	7,6	85	1" 1/4 F	131020

Max. particles 5 mm for Nova 180, 10 mm for Nova 300 - Includes 5 m cable.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Nova-up 300 MAE	210	1~230	1,5	9	7,6	86	1" 1/4 M	131123
Nova-up 600 MAE	520	1~230	3,4	12,9	9,8	150	1" 1/4 M	131133

Electronic level detection - 5 mm suction height - Max. particles 10 mm - Includes 10 mm cable - Vertical outlet.

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Nova-up 600 automatic	520	1~230	3,4	13	9,8	150	1" 1/4 M	131090

Max. particles 10 mm - Includes 10 m cable - Vertical outlet.



Sewage pump



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	min. suction level (mm)	outlet Ø	code
Feka 600 automatic	550	1~230	4,3	12	7,4	175	1" 1/4 F	131102

Passing through 25 mm - Includes 5 m cable.



Well pumps



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. height (m)	max. submersion depth (m)	pump Ø (mm)	outlet Ø	code
Divertron 1000	550	1~230	3,8	4,2	34	15	150	1" F	152599
Divertron 1000-X*	550	1~230	3,8	4,2	34	15	150	1" F	152600
Divertron 1200	750	1~230	4,8	4,2	43	15	150	1" F	152601
Divertron 1200-X*	750	1~230	4,8	4,2	43	15	150	1" F	152602

Built-in automatic device with lack of water protection & check valve - Includes 15 m cable.

* For connection to rain water collecting tank.



Suction set for rainwater collecting tank

Includes strainer basket & floating ball.

length (m)	code
1,5	355253
3	355237
20	550504

Rope



Wastewater lifting stations


According to European Standard EN 12050-2.

Complete set for wastewater (after wastewater tank or sand filter)

Ø 600 underground installation high density polyethylene tank - 1/4 turn closing cover - DR Steel 37 pump, 1~230V-50Hz, passing through Ø 10 mm - 100 mm PVC inlet, 1"1/4 male threaded outlet, 50 mm PVC aerator, 50 mm PVC wire outlet - Check valve - 1"1/4 ball valve.



	tank (l)	H (mm)	E (mm)	A (mm)	max. flow (m³/h)	max. height (m)	code
Altibox CE 650/600	170	650	200	175	9	13,8	131540
Altibox CE 850/600	210	850	400	270	9	13,8	131541
Altibox CE 1100/600	300	1100	660	270	9	13,8	131542
Altibox CE 1400/600	360	1400	950	270	9	13,8	131543
Altibox CE 1850/600	480	1850	1400	270	9	13,8	131544
Altibox CE 2500/600	650	2500	2050	270	9	13,8	131545



		code
Outlet flexible hose 1"1/4		453135
		code
Extension for Altibox 600	300 mm height - 3 waves closing.	452999
		code
Sawing set DN100	Includes hole saw, gasket & cap.	453067
		code
Tight connection set	For tight connection up to 5 connectors 1,5 to 6 mm².	432106

Complete set for wastewater

Not for sewage & dirty water (toilets, etc...) - 30 l tank - Nova 300 automatic pump, 1~230V-50Hz, max. particles 5 mm - Float valve - Check valve - Dimension (mm): L 408 x l 310 x H 360.

	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	tank (l)	code
Novabox 30/300	220	1~230	9	7,1	30	131450



Sewage & dirty water lifting stations

According to European Standard EN 12050-1 - With foot peg and guide bars.

Indoor & outdoor installation

1 pump

Underground installation 270 l polyethylene tank - 12 screws closing cover - Composite guide bar device - 100 mm PVC inlet, 63 mm PVC outlet, 50 mm PVC aerator, 50 mm PVC wire outlet, 2 gland packs - Dimension (mm): L 800 x l 640 x H 940 - SEMISOM 290 automatic or 490 automatic pump, 1~230V-50Hz, with Vortex impeller, 10 m wire, passing through Ø 50 mm - 1 mounted 2" PVC ball check valve.

	Power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	tank (l)	code
Fekafos DSD 270 PP/290 automatic	550	1~230	12	8	270	145010
Fekafos DSD 270 PP/490 automatic	550	1~230	27	10,5	270	145011

2 pumps

Underground installation 270 l polyethylene tank - 12 screws closing cover - Composite guide bar device - 100 mm PVC inlet, 63 mm PVC outlet, 63 mm PVC aerator, 50 mm PVC wire outlet - Dimension (mm): L 800 x l 640 x H 940 - DR2P control panel for 2 pumps to be mounted at installation - 2 level controls for pumps - 2 SEMISOM 290 pumps, 1~230V-50Hz, with Vortex impeller, 10 m wire, passing through Ø 50 mm - 2 mounted 2" cast iron ball check valves.

	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	tank (l)	code
Bifos DR2P 270 PP/290 M	550	1~230	12	8	270	145020

	height (mm)	code
Extension for DSD & DR2P	300	453018

Outdoor installation

Underground installation 270 l polyethylene tank - Ø 585 mm cover - 1/4 turn cover - Screws locking - Composite guide bar device - Foot peg welding without drilling - 2" cast iron check valve, 2" PVC valve - 180° inlet water from 200 to 500 mm, thanks to supplied drilling set - 100 mm PVC inlet, 63 mm PVC outlet, 50 mm PVC aerator, wire outlet - Dimension (mm): L 785 x l 590 x H 1025 - SEMISOM 290 automatic or 490 automatic pump, 1~230V-50Hz, with Vortex impeller, 10 m wire & control panel, passing through Ø 50 mm.

	power supply (W)	voltage (V-50Hz)	max. flow (m³/h)	max. height (m)	tank (l)	code
Fekafos Enter 271 PP/290 automatic	550	1~230	12	8	270	145000
Fekafos Enter 271 PP/490 automatic	1100	1~230	29	10	270	145001

	height (mm)	code
Extension for Fekafos Enter	200	452991
	400	452992

Accessories

HidroTOM
 1152 Budapest, Városcapu u. 3.
 Tel./Fax: +361415-0802, -03 Mobil: +36309449620
 www.hidrotom.hu, E-mail: hidrotom@hidrotom.hu
 5350 Tiszafüred Őz u. 15.

	code
Sawing set DN110	412619
	code
Connection set PVC 110/100	453117



■ Toilet macerators



According to European Standard EN 12050-3.

IP44 - Connection set for outlet 22 to 40 mm - Tank adapted to 4,6 to 9 l water volume - Easy maintenance & access to motor, pump, macerator & pressure switch - Silent - Power supply 490 W - 1~230V-50Hz - 2,3 A - Max. flow 115 l/mm - Max. height 8 mm - Includes check valve - Dimension (mm): L 456 x l 178 - H 352.



Genix 110 Genix 110 comfort*

For 1 WC + 1 sink.

code
131460
131461

* Lower sound rating: less than 60 dB.

Genix 130 Genix 130 comfort*

For 1 WC + 1 sink + 1 shower + 1 bidet.

code
131462
131463

* Lower sound rating: less than 60 dB.

Connection set

Includes 500 mm pipe, gear clamp & fitting.

code
451021

■ Greases separators with sludge trap

Restaurants & collective use - According to European Standard EN 1825-1 - High density polyethylene tank - 110 mm PVC inlet & outlet - Tight polyethylene cover - Ø 620 cover - Underground & above ground installation.

NEW



	max. meals/day		flow (l/s)	separator volume (l)	sludge trap volume (l)	dimension (mm)	code
	restaurant	canteen					
YGO500E	100	220	1	240	100	L 1000 x l 1000 x H 1000	457340
YGO501E	150	330	1,5	510	150	L 1200 x l 1200 x H 1230	457660
YGO502E	200	440	2	490	200	L 1200 x l 1200 x H 1230	457690

code
453026
453027

Extension 200 mm Extension 400 mm

Restaurants & collective use - Stainless steel tank - Drain column - Tight cover - Above-ground installation.



	max. meals/day	volume (l)	dimension (mm)	code
Sepinox 340	100	340	L 1260 x l 640 x H 890	456519
Sepinox 680	200	680	L 1510 x l 680 x H 1190	456520

■ Greases separators - Dishwashing

Restaurants & collective use.

MINIGR

Stainless steel tank - 33/42 inlet & outlet with clamp - Tight stainless steel cover - Drainage with 1" valve & cap - 55 l volume - Max. flow 0,75 l/s - Dimension (mm): L 510 x l 410 x H 415.

code
456514

Restaurants & collective use.

GM1 E

High density polyethylene tank - PVC inlet & outlet - Tight polyethylene cover - Stainless steel screws - 55 l volume - Max. flow 0,75 l/s - Dimension (mm): L 600 x l 435 x H 450.

code
456517

Drainage valve

For polyethylene separator.

code
658450

■ Greases tank

Single family kitchen use - 200 l high density polyethylene tank - 410 mm tight cover - Underground installation - 110 mm connection - Built-in removable trap - Dimension (mm): L 1000 x l 585 x H 715.

GM2 E

code
456518

Liquid transfer pumps



For clear water, salty water, wine, vinegar, milk.



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (l/mn)	max. height (m)	code
BE - M 20	340	1~230	1,8	27	20	093020
BE - M 25	710	1~230	3,3	40	14	093025
BE - M 30	800	1~230	3,7	76	14	093030
BE - T 30	800	3~400	1,5	76	14	093035
BE - M 40	950	1~230	4	116	20	093040
BE - T 40	1000	3~400	3	116	20	093045
BE - M 50	2100	1~230	11	202	24	093050
BE - T 50	1900	3~400	5,1	202	24	093055

	power supply (W)	voltage	amp. (A)	max. flow (l/mn)	max. height (m)	code
Marina 20 - 12V	350	12V DC	25	27	18	093070
Marina 20 - 24V	350	24V DC	13	27	18	093080

	power supply (W)	voltage	amp. (A)	max. flow (l/mn)	max. height (m)	code
Novax - 20B	340	1~230	1,8	27	20	093058

	code
Drill 20 for drilling machine With strainer basket	093100

Oil transfer pumps



	power supply (hp)	voltage (V-50Hz)	amp. (A)	max. flow (l/h)	code
Viscomat 70 M	1	1~230	4,6	1500	090100
Viscomat 70 T	1	3~400	2,2	1500	090105
Viscomat 90 M	1	1~230	6,2	3000	090110
Viscomat 90 T	1	3~400	5	3000	090115

Gas oil transfer pumps



	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. pressure (bar)	code
Panther 56 Filter	370	1~230	2,2	3,5	1,7	090012

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (m³/h)	max. pressure (bar)	code
Panther 72 Filter	500	1~230	4,2	4,8	1,9	090007

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (l/mn)	max. pressure (bar)	code
Cube 56/33	370	1~230	2,2	50	1,7	090009
Cube 70/33	500	1~230	4,2	70	1,9	090017
Cube 56/33 CFD*	370	1~230	2,2	50	1,7	090019
Cube 70/33 CFD*	500	1~230	4,2	70	1,9	090023

* Includes CFD water absorber filter.

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (l/mn)	max. pressure (bar)	code
Station ST Panther 56	370	1~230	2,2	50	1,7	090002
Station 56/33 Diesel	370	1~230	2,2	50	1,7	090003

	power supply (W)	voltage (V-50Hz)	amp. (A)	max. flow (l/mn)	max. pressure (bar)	code
Station P56 Filter GO	370	1~230	2,2	50	1,7	090064
Station P72 Filter GO	500	1~230	4,2	70	1,9	090065



Carry 3000 12V
Carry 3000 24V

power supply (W)	voltage	max. flow (m³/h)	Max. pressure (bar)	code
260	12V DC	2,4	1,9	090021
260	24V DC	2,4	1,9	090031



Battery set 3000 12V
Battery set 3000 24V

power supply (W)	voltage	max. flow (m³/h)	Max. pressure (bar)	code
260	12V DC	2,4	1,9	090041
260	24V DC	2,4	1,9	090051



Panther 56 DC 12V
Panther 72 DC 24V

power supply (W)	voltage	max. flow (m³/h)	Max. pressure (bar)	code
370	12V DC	3,5	1,7	090014
500	24V DC	4,8	1,9	090015



Piusibox 12V
Piusibox 24V

power supply (W)	voltage	max. flow (m³/h)	Max. pressure (bar)	code
260	12V DC	2,4	1,9	090060
260	24V DC	2,4	1,9	090061



Litre meter

Precision ± 1% - Fittings Ø 1" F - Max. pressure 3,5 bar.

code

530010



Gas oil nozzle

Free nut Ø 1" F & hose nozzle Ø 20 mm -
Max flow 60 l/mn.

code

530020



**Gas oil nozzle
w/ automatic shut-off**

Free nut Ø 1" F & hose nozzle Ø 20 mm -
Max. flow 60 l/mn - Min. pressure 0.4 bar.

code

530025



Discharge pipe

Ø 20 mm with welded fittings MM 1".

4 m

code

530031



Suction pipe

Ø 25 mm with welded fittings MM 1".

1 m

1,5 m

2 m

code

530026

530027

530028



Hose nozzle

M 1" for Ø 20 mm.

M 1" for Ø 25 mm.

code

453056

453057



Filter

Ø 3/4" M - 1" F & hose nozzle.

code

530050



Suction pipe

M 1" - Adjustable length 50 to 90 cm.

code

530033



Presscontrol
Stainless steel fitting set

For Panther 56 & 72 - 1~230V (50Hz) - Fitting M 1".
Socket MM 1" & elbow 1".

code

416003

453014

For surface pumps



Control, overcurrent & lack of water protection

For 1~230V & 3~400V pumps - 1 to 10 A (4 kW for 3~400V - 1,1 kW for 1~230V).

Protec 2

Protec 2 with forced motion switch

For use with reversed contactor.

code

474000

471550

For 1 pump drainage/sewage/dirty water

Control & protection



Max. 10 A - For 1~230V & 3~400V pumps - Needs 1 or 2 level switches - On/off switch & forced motion switch - Built-in sound alarm - Connection Ipsotherm.

Protec 2 Releage

code

474002



For clear & slightly dirty water. For 1~230V pumps - Max. 6 A with 2 electrodes - Includes 2 electrodes & 30 m cable.

Micro DSN 22

code

471029


HidroTOM
1152 Budapest, Városcapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidrotoom.hu, E-mail: hidrotoom@hidrotoom.hu
5350 Tiszafüred Őz u. 15.

For 2 pumps drainage/sewage/dirty water

Control & protection



For 1~230V & 3~400V pumps - Adjustable 1,6 to 10 A - Needs 3 level switches - Built-in sound alarm - Connection Ipsotherm.

Protec 4+/10RF

code

474004

For well & borehole pumps

Control & lack of water protection



For 1~230V pumps up to 6,5 A - Full automatic - No accessories requested.

Micro DSE 1~230V

code

471511

For 1~230V & 3~400V pumps up to 10 A - Includes electrode & 40 m wire.

Micro DSN 1~230V & 3~400V

code

471050JE

Motor protection & level monitoring (for 1~230V & 3~400V pumps).



Full automatic - No accessories requested.

DSE 12 1~230V	With contactor up to 12 A.
DSE 18 1~230V	With contactor up to 18 A.
DSE 10 3~400V	With contactor up to 10 A.
DSE 18 3~400V	With contactor up to 18 A.

code

471500
471505
471501
471502



Mono-electrode with automatic variable transmission delay - Electronic card sold separately.

DSN 51/12 3~400V	With contactor up to 12 A.
DSN 51/18 3~400V	With contactor up to 18 A.
DSN 51/25 3~400V	With contactor up to 25 A.
DSN 51/40 3~400V	With contactor up to 40 A & built-in disconnecter.
DSN 51/0	Without contactor. With DIN rail connection for contactors up to 12 A.
Card DSN 51	

code

471112
471118
471125JE
471140
471100JE
471711



Bi-electrode with critical level detection - Electronic card sold separately.

DSN 52/12 3~400V	With contactor up to 12 A.
DSN 52/18 3~400V	With contactor up to 18 A.
DSN 52/25 3~400V	With contactor up to 25 A.
DSN 52/40 3~400V	With contactor up to 40 A & built-in disconnecter.
DSN 52/0	Without contactor. With DIN rail connection for contactors up to 12 A.
DSN 52/12 reversed	Reversed control for filling tank monitoring.
Card DSN 52	

code

471212
471218
471225
471240
471200JE
471213
471714



Water level control (for pools, basins, reservoirs, ...).

For 1~230V pumps - Outlet 24V-17 VA or dry contact 5 A.

Danaide

code

471450



Control panel accessories



Overvoltage protection PS3	For DSN, PAD, Protec 2 & 4 - For 1~230V & 3~400V pumps - Max. 24 A - Resists at chocks up to 7 kVA.
Spare cartridge PS3	

code

433000
937813

DSN electrode
Stainless steel electrode
Cable*

For electrode - 1 x 1,5 mm² - Food quality & safety.

code

414000
414010
431600

* price/meter



Sound alarm
Sound alarm with
36 hours running reserve

Noise intensity 90 dB - 1~230V.

code

471701
471702



Connection set 3C	For 3 connectors (1~230V) - IP67.
Connection set 4C	For 4 connectors (3~400V) - IP67.

code

432102
432104



Membrane tanks

2 years Guarantee - EC according to PED-97/23 - Pre-set pressure: 2 bar - Temperature: -10°C to +90°C - Food quality & safety membrane.



Standard

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	Ø tank (mm)	code
5	V	10	1"	320		160	301005JE
8	V	10	1"	335		200	302008JE
19	V	10	1"	410		270	301019

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	Ø tank (mm)	code
24	V	10	1"	340		350	301024

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	Ø tank (mm)	code
20	V	10	1"	495		250	301020

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	Ø tank (mm)	code
20	H	10	1"		500	250	303020
40	H	10	1"		560	345	303040
60	V	10	1"	815		380	309060
60	H	10	1"		650	380	309061
80	V	10	1"	790		450	309080
80	H	10	1"		640	450	309081
100	V	10	1/2" & 1"	910		450	309100
100	H	10	1/2" & 1"		750	450	309101
200	V	10	1/2" & 1 1/2"	1215		554	309200
200	H	10	1/2" & 1 1/2"		1020	554	309201
300	V	10	1/2" & 1 1/2"	1375		625	309300
300	H	10	1/2" & 1 1/2"		1190	625	309301
500	V	10	1/2" & 1 1/2"	1460		775	309500
750	V	10	1/2" & 1 1/2"	1925		790	309750
1000	V	10	1/2" & 2"	1915		935	309900

H: horizontal

V: vertical

HidroTOM
1152 Budapest, Városcapu u. 3.
Tel./Fax: +361415-0802, -03 Mobil: +36309449620
www.hidroto.hu, E-mail: hidroto@hidroto.hu
5350 Tiszafüred Öz. u. 15.

High pressure

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	Ø tank (mm)	code
20	V	16	1"	485	250	308020
100	V	16	1/2" & 1"	915	464	309103
200	V	16	1/2" & 1 1/2"	1220	556	309203
300	V	14	1/2" & 1 1/2"	1370	626	309303
495	V	12	1/2" & 1 1/2"	1461	777	309503

20 l

100 l to 495 l

Membranes on request for all types of varem tanks





Diaphragm tanks



5 years guarantee - No maintenance required - EC according to PED-97/23.

Challenger

Max. temperature: 90°C - Stainless steel 316 connections.



volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	code
8	V	10	1"	315		305008JE
18	V	10	1"	370		305018
18	V	16	1"	370		305019
24	V	10	1"	440		306024

Pre-set: 1,9 bar.



H: horizontal

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	code
20	H	10	1"	440		305020
60	H	10	1"	530		305060
80	H	10	1"	730		305080
100	H	10	1"	720		305101


Pre-set: 1,9 bar.



V: vertical

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	length (mm)	code
60	V	10	1"	620		305059
80	V	10	1"	815		305079
100	V	10	1"	805		305100
150	V	10	1"	820		305150
200*	V	10	1 1/4"	1034		306201
240*	V	10	1 1/4"	1201		306240
310*	V	10	1 1/4"	1488		306310
450*	V	10	1 1/4"	1505		306450

Pre-set: 1,9 bar; except * 2,6 bar.




C2-Lite

Fiberglass tank: leight weight - Max. temperature: 50°C.

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	weight (kg)	code
60	V	8,6	1"	649	9	318060
100	V	8,6	1"	967	12	318100
130	V	8,6	1"	1227	15	318130
250	V	8,6	1 1/4"	1303	25	318250
350	V	8,6	1 1/4"	1448	33	318350
450	V	8,6	1 1/4"	1831	37	318450

Pre-set: 1,4 bar.



AWB

All weather for outdoor installation - Carbon steel tank with polypropylene shell - Stainless steel connection.

volume (l)	type	max. pressure (bar)	Ø connection M	height (mm)	weight (kg)	code
18	V	10	3/4"	425	5,3	318018
24	V	10	1"	454	6,2	318024

Pre-set: 1,9 bar.



NEW



Connection set GC

Includes flexible hose 500 mm - 1", 5 ways fitting, pressure switch XMP 6 PM, manometer 0-6 radial, teflon roll.

code
455090

NEW



Standard

ΔP adjustable - Pre-set: 1,4 to 2,8 bar - Fitting F 1/4" - 230V 16A.

code

003170



Standard + wire

Pre-set: 2 to 3,5 bar - Fitting F 1/4" - Supplied with wire - 230V 16A.

code

003121



XMP 6 bipolar

Max. pressure: 6 bar - Min. ΔP : 0,6 bar - Pre-set: 1,4 to 2,8 bar -
Max. power: 1,5 kW (for 1~230V) - Fitting F 1/4" -
Temperature: 0 to 70°C - Wired with standard take-off.

code

412500

XMP 6 wired bipolar

Same as XMP 6 bipolar, except: wired included.

412501



XMP 6 PM bi/tripolar

Max. pressure: 6 bar - Min. ΔP : 0,6 bar. Pre-set: 2 to 3,5 bar -
Max. power: 3 kW (for 3~400V) - Fitting F 1/2" -
Manometer outlet F 1/4" - Temperature: 0 to 70°C.

code

412506

XMP 12 PM bi/tripolar

Same as XMP 6 PM, except: max. pressure: 12 bar, min. ΔP : 1 bar, pre-set: 4 to 6 bar.

412512



XMx Reversed with manometer inlet

Lack of water switch-off device - Pre-set: 0,5 to 1,5 bar - Usable only with remote control - Fitting F 1/2" - Manometer outlet F 1/4" - Temperature: 0 to 70°C - Max. pressure: 6 bar.

code

412560



69 WEC bipolar with switch & lack of water protection

Max. pressure: 4,5 bar - Min. ΔP : 0,9 bar - Pre-set: 1,3 to 2,6 bar -
Max. power: 1,1 kW (for 1~230V) - Fitting F 1/4" -
Low pressure (0,4 bar) switch-off device.

code

412550



69 WR3 Reversed

Lack of pressure switch-off device - Pre-set: 0,3 to 0,7 bar -
Max. power: 1,5 kW (for 1~230V) - Fitting F 1/4".

code

412552



MCS 11 Universal unipolar

Lack of water switch-off device - Pre-set: 0,2 to 0,5 bar - Usable only with remote control - Fitting F 1/4" - Temperature: -25°C to 80°C - Max. pressure: 11 bar - Protection IP55.

code

410501

MCS 22

Same as MCS 11, except max. pressure: 22 bar.

410502



ELT

Pressure setting: -0,2 - 8 bar - Differential pressure: 0,6 - 3 bar.
Pressure setting: 5 - 16 bar - Differential pressure: 1 - 3,5 bar.
Pressure setting: 5 - 28 bar - Differential pressure: 2 - 10 bar.
Pressure setting: 5 - 50 bar - Differential pressure: 2 - 15 bar.

code

132001SE
132002SE
132003
132004



More informations page 128.



3 way fitting

Ø

1" FF 1"

code

BB11-008



81 mm



92 mm

5 way fitting

Ø

1" FF 1" - F 1/4" - M 1/4"

1" FF 1" - F 1/4" - M 1/4"

height
(mm)

code

81

RP5V

92

BB11-007



Plastic suction set

PVC pipe - Food quality & safety - Includes Plastic check valves & strainer.

length (m)	Ø pipe	Ø	code
4	22	F 1"	003000
7	22	F 1"	003005



Brass suction set

PVC pipe - Food quality & safety - Includes brass check valve & stainless steel strainer.

length (m)	Ø pipe	Ø	code
5	22	F 1"	003010
7	22	F 1"	003020



Metal suction set

PVC pipe - Food quality & safety - Includes brass fitting & check valve, stainless steel strainer, aluminium socket.

length (m)	Ø pipe	Ø	code
7	25	F 1"	003025
7	30	F 1 1/4"	003030



Universal drainage set

For all drainage/sewage/dirty water pumps
PVC pipe.

length (m)	Ø pipe	Ø	code
5	25	F 1 1/4"	002200
5	32	F 1 1/2"	002205



Discharge set

DN50 - 2" camlock fitting -
Male or female nipple to be mounted on the pump.

length (m)	code
10	454509



Flat discharge pipe

PVC - Symmetrical fittings at both ends -
Temperature: -10°C to 60°C - Pressure 8 bar at 20°C.

DN	length (m)	code
50	10	454510
50	15	454515
80	10	454511



Discharge set

For outlet Ø 53/63 - Bore 50 - Includes check ball valve, fitting MM 2",
PVC ball valve with full bore & 2 end fittings.

code

455010

Valve set

Same as discharge set but without check ball valve.

455011



PVC check ball valve

Ø

1 1/4" Threaded FF - Max. pressure: 10 bar - PVC body & ball -
1 1/2" Max. temperature: 60°C.

2"

2 1/2"

3"

code

334007

334008

334009

334010

334011

■ Dry - ABS plastic box

Ø 50 - Axial



pressure (bar)	Ø connection	code
0 - 4	1/4"	MA04
0 - 6	1/4"	413006TH
0 - 10	1/4"	MA10

Ø 50 - Radial



pressure (bar)	Ø connection	code
0 - 4	1/4"	MR04
0 - 6	1/4"	413106
0 - 10	1/4"	MR10

Ø 80 - Radial



pressure (bar)	Ø connection	code
0 - 4	1/2"	M80R04
0 - 10	1/2"	M80R10

Ø 63 - Axial



pressure (bar)	Ø connection	code
0 - 6	1/4"	M63A06
0 - 10	1/4"	M63A10

Ø 63 - Radial



pressure (bar)	Ø connection	code
0 - 6	1/4"	M63R06
0 - 10	1/4"	M63R10

Ø 100 - Radial



pressure (bar)	Ø connection	code
0 - 6	1/2"	M100R06
0 - 10	1/2"	M100R10

■ Glycerin filled - Stainless steel box

Brass connection - Max. temperature: 60°C - Class 1,6 - Polycarbonate glass.

Ø 50 - Axial



pressure (bar)	Ø connection	code
0 - 2,5	1/4"	413203
0 - 6	1/4"	413206
0 - 10	1/4"	MA10G
0 - 16	1/4"	413216

Ø 50 - Radial



pressure (bar)	Ø connection	code
0 - 2,5	1/4"	413303
0 - 6	1/4"	413306
0 - 10	1/4"	MR10G
0 - 16	1/4"	413316

Ø 63 - Axial



pressure (bar)	Ø connection	code
0 - 2,5	1/4"	413403
0 - 6	1/4"	413406
0 - 10	1/4"	413410
0 - 16	1/4"	413416
0 - 25	1/4"	413425

Ø 63 - Radial



pressure (bar)	Ø connection	code
0 - 2,5	1/4"	413503
0 - 6	1/4"	413506
0 - 10	1/4"	413510
0 - 16	1/4"	413516
0 - 25	1/4"	413525

■ Manometer holder valves



Ø	pack	code
1/4"	50	ZRI08
3/8"	50	ZRI12
1/2"	25	ZRI15



Ø	code
1/4"	1306002
3/8"	1306003
1/2"	1306004



Push-button valve

Ø	code
1/4"	9880302
1/2"	9880304

Brass fittings,
see pages 181 to 186

Valves, strainers & check valves,
see pages 166 to 176

Flexibles hoses,
see pages 202 to 203

Float valves,
see page 42

Solenoid valves,
see page 88

